


AirLink Product Comparison



USE CASES

| | | | | | | | |
|-----------------------|---|---|--|--|---|--|---|
| Target Markets | Public Safety Field Service Mobile Data | Public Safety Field Service Mobile Data | Automatic Vehicle Location (AVL) Mobile Resource Management (MRM) | Infrastructure Utilities Sales and Payment Networking | Infrastructure Sales and Payment Security Networking | Utilities Automation | Sales and Payment Networking Infrastructure |
| Applications | Field Force Automation Mobile Office Fleet Management Mobile Hotspot | Field Force Automation Mobile Office Fleet Management | Fleet Management Asset Tracking Vehicle Telemetry | Point-of-Sale Vending / Kiosks Video Surveillance Remote Monitoring/Control | Point-of-Sale Vending / Kiosks Video Surveillance Banking / ATM Business Continuity | Energy Management Industrial Automation SCADA / Telemetry Intelligent Traffic Systems | Wireline Replacement Business Continuity Multiple Point-of-Sale Groups of Kiosks/Vending Video Surveillance |

WIRELESS TECHNOLOGIES [all devices have fallback to earlier technologies]


| | | | | | | | | |
|----|---------------|---|---|---|---|---|---|---|
| 2G | GPRS | | | • | | | • | |
| 3G | HSPA | • | • | | • | • | | • |
| | CDMA EV-DO | • | • | • | • | • | • | • |

PRODUCT FEATURES

| | | | | | | | |
|---|--------------------------------------|------------------|------------------|------------------|------------------|------------------|-----------------------|
| Connection Status LED Indicators | 4 LED Indicators | 6 LED Indicators | 3 LED Indicators | 5 LED Indicators | 4 LED Indicators | 4 LED Indicators | 7 LED Indicators |
| Reset Button | • | • | • | • | • | • | • |
| Machine Protocols | • | • | | • | | • | |
| GPS | • | • | • | | | | |
| Operating Temperature | -30°C to +70°C | -30°C to +70°C | -30°C to +70°C | -30°C to +70°C | -30°C to +70°C | -30°C to +70°C | 0°C to +50°C |
| Power Consumption | Non Wi-Fi: 165 mA* Wi-Fi: 240 mA* | 330 mA* | 250 mA* | 235 mA* | 110 mA* | 350 mA* | 380 mA* |
| Low Power Mode | • | • | • | | | | |
| Input Voltage | 9 - 36 V DC | 9 - 28 V DC | 9 - 28 V DC | 9 - 28 V DC | 9 - 28 V DC | 9 - 28 V DC | 7 - 20 V DC |
| Wi-Fi | 802.11 b/g (optional) | | | | | | 802.11 b/g (optional) |
| Class 1 Div 2 | | | | • | • | • | |
| MIL Standard | 810-F | 810-F | 810-F | 810-F | 810-F | 810-F | |

* Based on typical test scenarios, actual performance may vary

AirLink Product Comparison



CONNECTIONS

| | | | | | | | |
|-----------|---|------------------------------------|-----------------------------|--------|--------------|--------------|--------------------|
| Serial | DB9 | DB9 | DB9 (optional) | DB9 | | DB9 | |
| Ethernet | 10/100 | 10/100 | | 10/100 | 10/100 | | 10/100 - Qty 2 |
| USB | Type B | Type B | 2.0 Mini B-5 | | 2.0 Mini B-5 | 2.0 Mini B-5 | 2.0 Type A - Qty 2 |
| I/O Ports | 2 Programmable/ 2 Digital/ 4 Analog | 4 Digital/ 4 Analog/ 2 Relay | 6 Programmable/ 4 Analog | | 2 Digital | 2 Digital | |

ANTENNA TYPES

| | | | | | | | |
|--------------|-----|-----|-----|-----|-----|-----|-----|
| RF | TNC | TNC | SMA | SMA | SMA | SMA | SMA |
| Rx Diversity | SMA | SMA | | SMA | SMA | | SMA |
| GPS | SMA | SMA | SMA | | | | |

SECURITY

| | | | | | | | |
|--------------|---|---|---|---|---|---|---|
| IPsec VPN | • | • | • | • | • | • | • |
| Firewall | • | • | • | • | • | • | • |
| WPA/WPA2-ENT | • | | | | | | • |

ROUTING

| | | | | | | | |
|-----------------|---|---|---|---|---|---|---|
| Port Filtering | • | • | • | • | • | • | • |
| NAT | • | • | • | • | • | • | • |
| DHCP | • | • | • | • | • | • | • |
| GRE | • | • | • | • | • | • | • |
| WAN Failover | | | | | | | • |
| Port Forwarding | • | • | • | • | • | • | • |
| VLAN/VRRP | | | | | | | • |
| SNMP | • | • | • | • | • | • | • |

SOFTWARE FEATURES

| | | | | | | | |
|---------------------|--------|--------|--------|--------|--------|--------|--------|
| ALEOS™ Intelligence | • | • | • | • | • | • | • |
| Remote Management | • | • | • | • | • | • | • |
| Events Reporting | • | • | • | • | • | • | • |
| Remote Diagnostics | • | • | • | • | • | • | • |
| AVL Support | • | • | • | | | | |
| Warranty | 3 year | 3 year | 1 year | 3 year | 1 year | 1 year | 3 year |

North America & Asia

Tel: +1 510 624 4200

Fax: +1 510 624 4299

Europe, Middle East & Africa

Tel: +44 20 8 622 3015

Fax: +44 20 8 622 3206

E-mail

AirLinkSales@sierrawireless.com

www.sierrawireless.com

P/N PRODCOMP031110



AirLink™

Sierra Wireless, the Sierra Wireless logo, AirLink, ALEOS and the red wave design are trademarks of Sierra Wireless. Other registered trademarks that appear on this brochure are the property of the respective owners. © 2010 Sierra Wireless, Inc. www.sierrawireless.com



AirLink Product Comparison